

332-1831-PRO

Dell® 332-1831 Compatible 65W 19.5V at 3.34A Black 7.4 mm x 5.0 mm Laptop Power Adapter and Cable

Features

- 7.4*5.0mm Tip Size
- Output Power: 65W
- Output Voltage: 19.5V
- Color: Black
- Operating Temperature: 0°C to 40°C
- Input Current:3.34A



Product Description

This is a Dell® 332-1831 compatible 65W 19.5V at 3.34A laptop power adapter specifically designed for Dell® notebooks. Our power adapters are 100% tested and compatible with the intended systems.

Specifications

Parameter	Specifications
Input Characteristics	
AC Input Voltage Rating	100VAC to 240VAC
AC Variation Range	90VAC to 264VAC
AC Input Frequency	50/60Hz
Variation Frequency	47/63Hz
Input Current	1.5A Maximum
Efficiency	More Than 83% (At 100V/240VAC/50Hz Input with Full Load)
Output Characteristics	
Output Power	65W
Output Voltage	19.5V
Output Current	3.34A
Tip Size	7.4*5.0mm
Turn On Delay Time	10 Seconds Maximum at 115Vac Input and Output at Maximum Load
Rise Time	40ms Maximum at 115Vac Input and Output Maximum Load
Hold Up Time	10ms Minimum at 115Vac Input and Output Maximum Load
Protection Features	
Short Circuit Protection	The power supply will be auto-recovered when short circuit faults are removed.
Over Current Protection	The power supply will be auto-recovered when faults are removed.
Over Voltage Protection	The power supply will not be auto-recovered until faults are removed.
Environmental Conditions	
Operating Temperature	0°C to 40°C, Full Load, Normal Operation
Storage Temperature	-20°C to 85°C
Relative Humidity	5% (0°C) to 90% (40°C) RH, 70 Hours, Full Load, Normal Operation

About Us:

Proline Options is one of North America's leading providers of transceivers and high speed cabling. With a reputation for quality, tested products that cover the connectivity spectrum, Proline Options has a solution for you regardless of the specification.

At Proline Options, every product is tested in its intended application - never batch or spec tested only. We run bandwidth, distance and IOS network tests. We have documented an impressive 0.03% failure rate over the last 10 years. To continue this rate of success we invest millions annually in our own on-site testing lab.



Tel: 855.933.3223
Email: sales@prolineoptions.com
Email: techsupport@prolineoptions.com Web:
<https://www.prolineoptions.com>