

### SFP-100-SM40-PRO

Alcatel-Lucent Nokia® SFP-100-SM40 Compatible TAA Compliant 100Base-LH SFP Transceiver (SMF, 1310nm, 40km, 0 to 70C, LC)

#### Features

- INF-8074 and SFF-8472 Compliance
- Duplex LC Connector
- Commercial Temperature 0 to 70 Celsius
- Single-mode Fiber
- Hot Pluggable
- Excellent ESD Protection
- Metal with Lower EMI
- RoHS Compliant and Lead Free



#### Applications:

- 100Base Ethernet
- Access and Enterprise

#### Product Description

This Alcatel-Lucent Nokia® SFP-100-SM40 compatible SFP transceiver provides 100Base-LH throughput up to 40km over single-mode fiber (SMF) using a wavelength of 1310nm via an LC connector. It is guaranteed to be 100% compatible with the equivalent Alcatel-Lucent Nokia® transceiver. This easy to install, hot swappable transceiver has been programmed, uniquely serialized and data-traffic and application tested to ensure that it will initialize and perform identically. It is built to meet or exceed the specifications of Alcatel-Lucent Nokia®, as well as to comply with MSA (Multi-Source Agreement) standards to ensure seamless network integration. This transceiver is Trade Agreements Act (TAA) compliant. We stand behind the quality of our products and proudly offer a limited lifetime warranty.

Proline's transceivers are RoHS compliant and lead-free.

TAA refers to the Trade Agreements Act (19 U.S.C. & 2501-2581), which is intended to foster fair and open international trade. TAA requires that the U.S. Government may acquire only "U.S. – made or designated country end products.



## Regulatory Compliance

- ESD to the Electrical PINs: compatible with MIL-STD-883 Method 3015.
- ESD to the Duplex LC Receptacle: compatible with IEC 61000-4-2.
- Immunity compatible with IEC 61000-4-3.
- EMI compatible with FCC Part 15 Class B EN55022 Class B (CISPR 22B) VCCI Class B.
- Laser Eye Safety compatible with FDA 21CFR 1040.10 and 1040.11 EN60950, EN (IEC) 60825-1,2.
- RoHs compliant with 2002/95/EC 4.1&4.2 2005/747/EC.

## Absolute Maximum Ratings

| Parameter                  | Symbol | Min. | Typ.    | Max. | Unit |
|----------------------------|--------|------|---------|------|------|
| Maximum Supply Voltage     | Vcc    | -0.5 |         | 4.0  | V    |
| Storage Temperature        | TS     | -40  |         | 85   | °C   |
| Operating Humidity         | RH     | 5    |         | 85   | %    |
| Operating Case Temperature | Tc     | 0    |         | 70   | °C   |
| Data Rate                  |        |      | 100/155 |      | Mbps |

## Electrical Characteristics (TOP=25°C, Vcc=3.3V)

| Parameter                     | Symbol | Min. | Typ. | Max. | Unit | Notes |
|-------------------------------|--------|------|------|------|------|-------|
| Power Supply Voltage          | Vcc    | 3.15 | 3.3  | 3.45 | V    |       |
| Power Supply Current          | Icc    |      |      | 300  | mA   |       |
| <b>Transmitter</b>            |        |      |      |      |      |       |
| Input differential impedance  | Zin    | 85   | 100  | 120  | Ω    | 1     |
| LVPECL Inputs (Differential)  | Vin    | 400  |      | 2000 | mVpp | 2     |
| <b>Receiver</b>               |        |      |      |      |      |       |
| Output Differential Impedance | Zout   | 85   | 100  | 120  | Ω    |       |
| LVPECL Outputs (Differential) | Vout   | 400  |      | 2000 | mVpp | 2     |

### Notes:

1. Rin > 100 kohms @ DC
2. AC coupled.

## Optical Characteristics

| Parameter                 | Symbol          | Min.                  | Typ. | Max.  | Unit | Notes |
|---------------------------|-----------------|-----------------------|------|-------|------|-------|
| <b>Transmitter</b>        |                 |                       |      |       |      |       |
| Average Output Power      | PO              | -5                    |      | 0     | dBm  | 1     |
| Optical Wavelength        | $\lambda$       | 1275                  | 1310 | 1350  | nm   |       |
| Spectral Width (RMS)      | $\Delta\lambda$ |                       |      | 3     | nm   |       |
| Optical Rise/Fall Time    | tr/tf           |                       |      | 2     | ns   | 2     |
| Extinction Ratio          | ER              | 10                    |      |       | dB   | 3     |
| Output Optical Eye        |                 | IUT-T G.957 Compliant |      |       |      |       |
| <b>Receiver</b>           |                 |                       |      |       |      |       |
| Receiver Sensitivity      | Pmin            |                       |      | -34.5 | dBm  | 4     |
| Receiver Overload         | Pmax            | -10                   |      |       | dBm  |       |
| Optical Center Wavelength | $\lambda_C$     | 1270                  |      | 1600  | nm   |       |
| LOS De-Assert             | LOSD            |                       |      | -35   | dBm  |       |
| LOS Assert                | LOSA            | -45                   |      |       | dBm  |       |
| LOS Hysteresis            |                 | 1                     |      |       | dB   |       |

### Notes:

1. Internally AC coupled.
2. 20%-80%
3. Filtered, measured with a PRBS  $2^{23}-1$  test pattern @155Mbps.
4. Minimum average optical power is measured at BER less than  $1E-12$ , with  $2^{23}-1$  PRBS and ER=9 dB

## Pin Descriptions

| Pin | Symbol      | Name/Descriptions  | Ref. |
|-----|-------------|--|------|
| 1   | VeeT        | Transmitter Ground (Common with Receiver Ground)               | 1    |
| 2   | TX Fault    | Transmitter Fault.   |      |
| 3   | TX Disable  | Transmitter Disable. Laser output disabled on high or open.    | 2    |
| 4   | MOD_DEF (2) | Module Definition 2. Data line for Serial ID.                  | 3    |
| 5   | MOD_DEF (1) | Module Definition 1. Clock line for Serial ID.                 | 3    |
| 6   | MOD_DEF (0) | Module Definition 0. Grounded within the module.               | 3    |
| 7   | Rate Select | No connection required.  |      |
| 8   | LOS         | Loss of Signal indication. Logic 0 indicates normal operation. | 4    |
| 9   | VeeR        | Receiver Ground (Common with Transmitter Ground)               | 1    |
| 10  | VeeR        | Receiver Ground (Common with Transmitter Ground)               | 1    |
| 11  | VeeR        | Receiver Ground (Common with Transmitter Ground)               | 1    |
| 12  | RD-         | Receiver Inverted DATA out. AC Coupled.                        |      |
| 13  | RD+         | Receiver Non-inverted DATA out. AC Coupled.                    |      |
| 14  | VeeR        | Receiver Ground (Common with Transmitter Ground)               | 1    |
| 15  | VccR        | Receiver Power Supply.   |      |
| 16  | VccT        | Transmitter Power Supply.                                      |      |
| 17  | VeeT        | Transmitter Ground (Common with Receiver Ground)               | 1    |
| 18  | TD+         | Transmitter Non-Inverted DATA in. AC Coupled.                  |      |
| 19  | TD-         | Transmitter Inverted DATA in. AC Coupled.                      |      |
| 20  | VeeT        | Transmitter Ground (Common with Receiver Ground)               | 1    |

### Notes:

1. Circuit ground is internally isolated from chassis ground.
2. Laser output disabled on TX Disable >2.0V or open, enabled on TX Disable <0.8V.
3. Should be pulled up with 4.7k-10kohms on host board to a voltage between 2.0V and 3.6V. MOD\_DEF (0) pulls line low to indicate module is plugged in.
4. LOS is open collector output. Should be pulled up with 4.7k-10kohms on host board to a voltage between 2.0V and 3.6V. Logic 0 indicates normal operation; logic 1 indicates loss of signal.



Pin-out of connector Block on Host board

### Recommended Circuit Schematic



### Mechanical Specifications

Small Form Factor Pluggable (SFP) transceivers are compatible with the dimensions defined by the SFP Multi-Sourcing Agreement (MSA).



### EEPROM Information

EEPROM memory map specific data field description is as below:



**About Us:**

Proline Options is one of North America's leading providers of transceivers and high speed cabling. With a reputation for quality, tested products that cover the connectivity spectrum, Proline Options has a solution for you regardless of the specification.

At Proline Options, every product is tested in its intended application - never batch or spec tested only. We run bandwidth, distance and IOS network tests. We have documented an impressive 0.03% failure rate over the last 10 years. To continue this rate of success we invest millions annually in our own on-site testing lab.



Tel: 855.933.3223

Email: [sales@prolineoptions.com](mailto:sales@prolineoptions.com)

Email: [techsupport@prolineoptions.com](mailto:techsupport@prolineoptions.com)

Web: <https://www.prolineoptions.com>